



ROOTGUIDE[®] ROLL DEEPER ROOTS

root guiding barrier

RootGuideRoll

Type S

Root guiding barrier

Application : top end equal to ground level.

Root guiding on roll offers fewer escape routes for roots as compared to short panels and is easy and fast to install. RootGuideRoll is there for ideal for long lengths parallel to an edging.

Standard available for various installation depths :

(Other heights available on request)

30 cm RootGuideRoll 030S

45 cm RootGuideRoll 045S

60 cm RootGuideRoll 060S

75 cm RootGuideRoll 075S

90 cm RootGuideRoll 090S

105 cm RootGuideRoll 105S

120 cm RootGuideRoll 120S

Material : recy polymer

Colour : black

Dimensions : 30 m per roll

Weight : 1 kg/m²

Design life : 100 years

** Bottom of the barrier to at least 10 cm below the zone of protection e.g., road foundation/obstacle/utilities etc*

Manufacturing in ISO-certified company. An ISO 9001 certificate shows that your organisation is customer-focused and committed to delivering consistent quality products.



Root guiding ribs

Function; guide roots deeper into the ground to ensure tree stability and protect other underground infrastructure.

- Vertical over the entire height
- Continuous from top to bottom
- At least 1 cm high
- Perpendicular to the wall
- Rib spacing 15 cm apart

Anti-lift ground lock tabs

Function; preventing panel being pushed up.

- Horizontally oriented
- Perpendicular to the wall
- Surface area per anchor >4 cm²
- Minimum 40 anchors per m² barrier

Barrier thickness

Function ; preventing root penetration.

- Thickness 1mm

RootGuideRoll is also available in 2mm thicknesses: RootGuideRoll type L

